

U N I V E R S A L C A B L E

A T r u e " M a d e i n J a p a n "



SL75R/75RR

SL-75R: 1.0m
SL-75R: 1.5m
SL-75RR: 1.0m pr
SL-75RR: 1.5m pr



SL75B

SL-75B: 1.0m
SL-75B: 1.5m



SL110XX

SL-110XX: 1.0m pr
SL-110XX: 1.5m pr

— Straight Line Series —

Our design philosophy is to simply eliminate coloration from cable itself. We never load it with character to create seemingly impressive sound, therefore avoid utilizing any special material, particular configuration nor special treatment to add some impressive feature. We passionately care for fundamental quality and spare no effort to realize it, but we believe it should always sound natural as if the cable does not exist.

Conductive core is; high purity oxygen free Copper, extensively annealed in low temperature, to remove mechanical distortion/stress from extrusion process for smoother electron transport due to uniformed internal structure.

SL75R/B; is Coaxial Interconnect cable, terminated with RCA or BNC plugs, usable for both Analogue and Digital (SPD/IF, Word Clock) with 75 ohm impedance, also genuine performer as the Visual Interconnect. Length: 1.0 m. and 1.5 m.

SL110XX; is Balanced 2-core Interconnect Cable, terminated with XLR plugs, usable for both Analogue and Digital (AES/EBU) with 110 ohm impedance. Length: 1.0 m. and 1.5 m.